

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

CERTIFICATION UNDER 37 C.F.R. 1.10

I hereby certify that this New Application Transmittal and the documents referred to as being enclosed therein are being deposited with the United States Postal Service on this date June 27, 2001 in an envelope as "Express Mail Post Office to Addressee", mailing label No. EK201385395US addressed to: Commissioner for Patents, Washington, D.C. 20231

William H. Meise June 27, 2001
William H. Meise date

MISSILE LAUNCHER CELL WITH EXHAUST GAS UPTAKE DUCTS, AND ARRAY OF SUCH MISSILE LAUNCHER CELLS

Field of the Invention

5 This invention relates to launchers for canisterized missiles, and more particularly to such launchers which are intended for placement below a protective deck for generally vertical launch.

Background of the Invention

10 Modern warships rely principally on missiles, rather than cannon, for their offensive and defensive armament. Thus, a warship may include a single automatic cannon, together with one or more batteries of missile
15 launchers. A battery of missile launchers may include a single missile launcher array at the rear deck of the ship, and two similar arrays on the foredeck.

20 A cluster of missile launchers for use on a ship may be similar to that described in U.S. Patent 5,837,917, issued November 17, 1998 in the name of McNab et al. McNab et al. describe a structure providing five vertical bays or "sleeves" of five juxtaposed missile

09892839 062701

launcher locations, held in a line array by muzzle-end, breech-end, and intermediate frames. Each sleeve of the missile launcher array of McNab et al. includes a support
5 lattice dimensioned to accommodate a canisterized missile. Protection against blast and environment is provided by a hard hatch assembly which includes a plurality of individually controllable or openable hatches,
10 each of which covers the end of one of the sleeves of the array. The breech ends of the sleeves open into a plenum, which is cooled by a water supply system. Cleats are provided for fastening the plenum to the underlying
15 structure. The missile canisters with which the McNab launchers are used include a frangible protective seal at the muzzle and breech ends, and also include a missile ready for launch, presumably together with an
20 electrical interface for providing information to the missile, if necessary, and for initiating the launch sequence as a result of external command. In order to use the McNab structure, one or more of the sleeve doors or
25 hatches is opened, and a canisterized missile is lowered thereinto. While not expressly stated, an umbilical is presumably used to connect the missile canister to a portion of the launch control system near the sleeve, so
30 that the missile may be remotely controlled. When that missile is to be launched, the door or hatch associated therewith is opened, and

09002839-062701

the corresponding hatch of a further one of the sleeves, which does not contain a canisterized missile, is opened. Missile firing is then commanded, as a result of which the missile within its container fires, expelling exhaust gases into the plenum and emerging from the muzzle end of the canister, breaking both frangible seals as it does so. The exhaust gases entering the plenum from the missile are cooled by water injection, which lowers the temperature of the exhaust gases to thereby reduce the infrared (IR) signature, reduce erosion due to the gas temperature, and in so doing generate a large amount of steam. The mixed steam and exhaust gases are routed from the plenum to above-decks by way of the vacant sleeve with its open hatch, used as a chimney.

If the support structure is a lattice, as McNab illustrates, a protective sleeve may run within that vacant one of the sleeves which is used as a chimney for exhaust gases/steam. The protective sleeve may include ablatable material for further protection.

Improved missile launchers are desired.

Summary of the Invention

A missile launcher cell according to an aspect of the invention is for accepting a canisterized missile which defines a missile launch end and a missile exhaust end, for, in use prior to missile launch, holding the missile canister in a generally vertical launch

09892839-062704

position below a deck. The missile launcher cell comprises at least one elongated exhaust gas chimney. It also comprises a support structure defining a generally axial cavity, also defining a missile launch end and a missile exhaust end. The cavity of the support structure has length and cross-sectional dimensions sufficient to accommodate the missile canister. The one or more exhaust chimneys lie along the exterior of the support structure and extend, parallel with the axis of the cavity, from near the missile launch end to near the missile exhaust end of the support structure. The missile launcher cell also includes a missile exhaust plenum attached to the support structure near the missile exhaust end of the support structure. The missile exhaust plenum is coupled to the one or more exhaust chimneys near the missile exhaust end of the support structure. The missile exhaust plenum further includes an attachment arrangement for attachment to the missile exhaust end of the missile canister, for routing missile exhaust gas from the missile exhaust end of the support structure to the one or more exhaust chimneys, for causing missile exhaust gas to vent from the one or more chimneys near the missile launch end of the support structure of the missile launcher cell.

A door structure is attached to the missile launch end of the missile launch cell support structure, for, in the closed state, protecting

In a particular embodiment of the invention, the cavity has a rectangular, or more particularly square, cross-section, and is dimensioned to accommodate a Mk 25 canisterized missile. The support structure may be a latticework. The number of chimneys in a particular embodiment is two, with the two chimneys running parallel with each other and with the cavity axis.

In a particular embodiment of the invention, the cavity has a rectangular, or more particularly square, cross-section, and is dimensioned to accommodate a Mk 25 canisterized missile. The support structure may be a latticework. The number of chimneys in a particular embodiment is two, with the two chimneys running parallel with each other and with the cavity axis.

structure and extend, parallel with the axis of the cavity, from near the missile launch end to near the missile exhaust end of the structure.

5 A missile exhaust plenum is attached to the support structure near the missile exhaust end of the support structure of each cell. The missile exhaust plenum of each cell is coupled to the one or more exhaust chimneys near the missile exhaust end of the support structure,
10 and also includes an attachment arrangement or means for attachment to the missile exhaust end of the missile canister, for thereby routing missile exhaust gas from the missile exhaust end of the support structure to the one or more
15 chimneys, for causing missile exhaust gas to vent from the at least one chimney near the missile launch end of the support structure. A door structure is attached to the missile launch end of the missile launch structure,
20 for, when closed, protecting at least the support structure and the one or more exhaust chimneys of the missile launcher cell, and any missile canister accommodated within the cavity of the cell, and for, when open, providing for
25 egress of the missile from its canister and exhaust gas from the one or more chimneys. This arrangement allows the array of missile launchers to be maintained in a condition in which all of the launcher cells are fitted with
30 canisterized missiles, without keeping at least one missile launch cell clear or unloaded so as to provide a chimney or path for the escape of

09692839-062701

exhaust gas from a missile fired in a missile
launch cell of the array. Thus, an aspect of
the invention lies in an array of launchers in
which a canisterized missile located within
5 each of (all of) the cavities of the array.

Brief Description of the Drawing

FIGURE 1 is a simplified perspective
or isometric view, partially cut away, of a
representative array of four individual missile
10 launcher cells according to an aspect of the
invention;

FIGURE 2 is a simplified perspective
or isometric view of a single missile launcher
cell of FIGURE 1;

15 FIGURE 3a is a simplified perspective
or isometric view illustrating details of the
deck portion and hatch near the missile launch
end of the missile launcher cell of FIGURE 2,
and FIGURE 3b is a corresponding detail of the
20 missile exhaust plenum near the missile exhaust
end of the missile launcher cell of FIGURE 2;

FIGURES 4a, 4b, and 4c are simplified
side elevation and plan views, respectively,
looking in mutually orthogonal directions, of
25 the missile launcher cell of FIGURE 2 with its
hatch open, showing the individual exhaust gas
management plenum, two exhaust gas chimneys or
uptakes extending from the plenum to the muzzle
or missile exit end of the launcher cell, and
30 the door assemblage covering the missile launch
exit and the chimneys;

FIGURE 5 is a simplified cross-

09492839.062701

sectional elevation view of the single missile launcher of FIGURE 2, showing the location of the missile within the missile canister and a portion of the gas management system, including the plenum and one chimney, and the deck door or hatch.

Description of the Invention

FIGURE 1 is a simplified perspective or isometric view of an array 10 of individual missile launcher cells 10a, 10b, 10c, and 10d, with portions of the structure cut away to reveal interior details. In FIGURE 1, the individual cells 10a, 10b, 10c, and 10d are identical to each other. Each cell includes a lattice-type support structure designated 12, thus missile launcher 10a includes a lattice-type support structure designated 12a, missile launcher cell 10b includes a lattice-type support structure designated 12b, missile launcher cell 10c includes a lattice-type support structure designated 12c, and launcher cell 10d includes a lattice-type support structure designated 12d. Each support structure 12 includes four "leg" portions. Taking missile launcher cell 10d of FIGURE 1 as being representative, three such legs can be seen, namely legs 14d1, 14d2, and 14d3, and the fourth leg is not illustrated. The illustrated legs of support structure 12a of missile launcher 10a are 14a1 and 14a2, the illustrated legs of support structure 12b of missile launcher 10b are 14b1 and 14b2, and the illustrated legs of support structure 12c of

09892839-062701

missile launcher 10c are 14c1 and 14c2. The legs of each support structure extend parallel with the missile launcher longitudinal axis; in particular, the various legs extend parallel to their corresponding launcher cell longitudinal axes 8a, 8b, 8c, and 8d.

A plurality of interconnecting support braces extend between the "legs" of the support structure of each missile launcher cell. As illustrated in FIGURE 1, representative support braces 20a1, 20a2, and 20a3 extend between leg elements 14a1 and 14a2.

The combination of these leg elements and support braces defines an elongated cavity (not clearly visible in FIGURE 1), having a rectangular or square cross-section, which extends vertically through each support structure 12a, 12b, 12c, and 12d. The cross-sectional dimensions of each such cavity are dimensioned to accommodate a canisterized missile, and to hold such canisterized missile in a vertical or about-vertical posture. In a particular embodiment in which the canisterized missile is a Mark 25 canisterized missile, the cross-section is ~~rectangular~~. **SQUARE**

A protective door or hatch assembly or structure is located at the upper or missile launch end of each missile launcher cell. More particularly, FIGURE 1 illustrates a hatch assembly 16a associated with missile launcher cell 10a, a hatch assembly 16b associated with missile launcher cell 10b, a hatch assembly 16c

6/21/01

09892839.062701

Each missile launcher cell 10a, 10b, 10c, and 10d of array 10 of FIGURE 1 also includes an a pair of missile exhaust gas uptake ducts or chimneys. In FIGURE 1, portions of the two chimneys associated with missile launcher cell 10a are designated 30a1 and 30a2, and portions of the corresponding chimneys of missile launcher cell 10b are designated 30b1 and 30b2, respectively. The chimneys associated with missile launcher cell 10c are designated 30c1 and 30d2, and those

associated with missile launcher cell 10d are designated 30d1 and 30d2 in FIGURE 1. The chimneys associated with each launcher cell extend from near the bottom, breech or missile exhaust end of each launcher cell to near the top, muzzle, or missile launch end of the launcher cell, and are generally parallel with the axis of the corresponding support structure. Thus, chimneys 30a1 and 30a2 extend parallel with the longitudinal axis 8a of missile launcher support structure 12a, chimneys 30b1 and 30b2 extend parallel with the longitudinal axis 8b of missile launcher support structure 12b, chimneys 30c1 and 30c2 extend parallel with the longitudinal axis 8c of missile launcher support structure 12c, chimneys 30d1 and 30d2 extend parallel with the longitudinal axis 8d of missile launcher support structure 12d. At their upper ends, the various chimneys or missile exhaust gas uptake ducts open into a region which lies under the doors or hatches of the corresponding missile launcher cell when that door or hatch is in its closed position. In FIGURE 1, the open ends of the two chimneys 30b1 and 30b2 are designated 18bc1 and 18bc2, respectively. The chimneys are preferably fastened to the corresponding deck plate, as by welding if the chimney is metallic, or by other suitable fastening method for other materials, as for example the chimneys 30b1 and 30b2 should be secured to deck plate 16bd. The corresponding

09892839.062701

hatch 16bh, when in its closed state, covers both the two chimney openings 18bc1 and 18bc2 and also the upper end of the elongated, vertically oriented cavity associated with or defined by the support structure 12b.

In addition to the chimneys, each missile launcher cell 10a, 10b, 10c, and 10d of array 10 is associated with an exhaust gas plenum or manifold. Thus, a plenum 40a is associated with missile launcher cell 10a, a plenum 40b is associated with missile launcher cell 10b, a plenum 40c is associated with missile launcher cell 10c, and a plenum 40d is associated with missile launcher cell 10d. Each exhaust gas plenum includes an attachment arrangement for attaching the plenum to the support structure. In a particular embodiment of the invention, the attachment arrangement also supports a "dogdown" arrangement which provides secure attachment of the plenum to the lower end of the canister of the canisterized missile used therewith. In FIGURE 1, the attachment arrangement for the exhaust gas plenum of each missile launcher includes four bosses or structures of a set 42 of bosses. Thus, exhaust gas plenum 40a of FIGURE 1 includes on its upper surface four attachment bosses, each of which is designated 42a, spaced around a rectangular or square exhaust gas inlet port 44a. Similarly, exhaust gas plenum 40b includes on its upper surface four attachment bosses, each of which is designated

09892839 "062701

42b, spaced around a square exhaust gas inlet
port 44b, exhaust gas plenum 40c includes on
its upper surface four attachment bosses, each
of which is designated 42c, spaced around a
5 square exhaust gas inlet port 44c, and exhaust
gas plenum 40d includes on its upper surface
four attachment bosses, each of which is
designated 42d, spaced around a square exhaust
gas inlet port 44d. Each of the bosses of set
10 42 is attached to the lower end of a leg of the
associated support structure. As an example,
the lower ends of the three vertically disposed
legs 14d1, 14d2, and 14d3 of support structure
12d of missile launcher 10d which are visible
15 in FIGURE 1 are attached to those three bosses
42d of plenum 40d which are nearest the viewer.
This effectively fastens the plenum 40d to its
associated support structure 12d, with axis 8d
of the elongated vertically-oriented cavity
20 (not designated in FIGURE 1) associated with
the support structure 12d overlying the missile
exhaust gas entry port 44d of the plenum 40d.

The chimneys or missile exhaust gas
uptake ducts of each missile launcher cell are
25 connected at their lower, missile exhaust, or
breach ends to corresponding apertures of the
associated plenum, so that missile exhaust
gases entering the plenum can be vented through
the chimneys to a location near the upper,
30 missile launch, or muzzle ends of the
structure. More particularly, the lower ends
of chimneys 30a1 and 30a2 of missile launcher

09892839.062701

10a are connected to corresponding apertures
46a1 and 46a2 of plenum 40a, the lower ends of
chimneys 30b1 and 30b2 of missile launcher 10b
are connected to corresponding apertures 46b1
5 and 46b2 of plenum 40b, the lower ends of
chimneys 30c1 and 30c2 of missile launcher 10c
are connected to corresponding apertures 46c1
and 46c2 of plenum 40c, and the lower ends of
chimneys 30d1 and 30d2 of missile launcher 10d
10 are connected to corresponding apertures 46d1
and 46d2 of plenum 40d. The chimneys are thus
supported at their lower ends by attachment to
their respective plenums, and may be attached
at their upper ends to their respective deck
15 plates. In addition, further attachments may
be made along their lengths to their respective
support structures.

FIGURE 2 is a simplified perspective
or isometric view of missile launcher cell 10d
20 of FIGURE 1, standing alone. Elements of
FIGURE 2 corresponding to those of FIGURE 1 are
designated by the same reference numerals. In
FIGURE 2, A portion of the drive mechanism
which controls the operation of hatch 16dh is
25 designated as 216. FIGURE 3a is a simplified
perspective or isometric view of the upper,
missile launch, or muzzle end 300 of the
missile launcher cell 10d of FIGURE 2. In
FIGURE 3a, elements corresponding to those of
30 FIGURE 2 are designated by the same reference
numerals. In FIGURE 3a, various sets of
apertures or holes defined in the edge of the

deck portion 16dd are designated 316da1,
316da2, 316da3, and 316da4. These sets of
apertures are provided for allowing the use of
bolts to fasten each deck portion to an
5 adjacent deck portion of another missile
launcher cell, in order to form an array such
as that illustrated and described in
conjunction with FIGURE 1, or to fasten the
deck portion of the cell to an adjacent deck
10 structure of the ship or other support
structure on which it is mounted, a cut-away
portion of which is illustrated in phantom as
390 in FIGURE 3a.

FIGURE 3b is a simplified perspective
15 or isometric view of a lower, missile exhaust
end, or breech end 380 of the missile launcher
structure of FIGURE 2, illustrating some
details of the structure. Elements of FIGURE
3b corresponding to those of FIGURE 2 are
20 designated by like reference numerals. In
FIGURE 3b, the structure of plenum 40d is seen
to include legs or supports 339a, 339b, and
339c, each of which defines a plurality of
plenum-to-ship mounting or attachment holes or
25 apertures 340d1, 340d2, and 340d3,
respectively. In addition, details of the
dogdown mechanism 360 include connecting drive
bars 350a and 350b.

In FIGURES 4a, 4b, and 4c, elements
30 corresponding to those of FIGURES 1, 2, 3a, and
3b are designated by the same reference
numerals. In FIGURE 4c, the aperture 418d

09892839-062701
102290-682660

represents the end of the elongated cavity defined by the support structure 12d, and it is centered on axis 8d, which appears as a dot in the view of FIGURE 4c. FIGURE 4b illustrates axis 8d as centered in the view, while FIGURE 4a shows axis 8d as off-center relative to the entire structure. Axis 8d appears as off center in FIGURE 4a because it is centered on the support structure 12d, which is offset relative to the entire missile launcher cell 10d because of the presence of the chimneys 30d1 and 30d2.

FIGURE 5 represents a cross-sectional view of missile launcher cell 10d of FIGURE 1 shown alone, and partially cut away to show the missile 512 and a missile canister 510, defining a missile launch end 510ML and a missile exhaust end 510ME, with the missile 512 contained within the canister 510. In FIGURE 5, the hatch 16dh is open.

Other embodiments of the invention will be apparent to those skilled in the art. For example, while the support structure 12x of a cell 10x of the FIGURES are illustrated as being of a particular form of lattice, other types may be used, or solid (non-lattice) portions may be used. While the missile launcher array of FIGURE 1 shows a linear array of missile launcher cells, the array can be rectangular, so that it includes a plurality of rows and columns, and it may intermix rectangular or square with linear arrays of

missile launcher cells. While the plenum associated with each missile launch cell has been shown as being roughly cubical, it may be drum-shaped (that is, a portion of a right circular cylinder) or semispherical (some portion of a sphere, including a hemisphere). While the missile canister has been described as containing a single missile, the missile canister can be of the type containing a plurality of missiles.

Thus, a missile launcher cell (any one of 12a, 12b, 12c, or 12d of array 10, with 12d taken as typical) according to an aspect of the invention is for accepting a canisterized missile (510, 512) which defines a missile launch end (510ML) and a missile exhaust end (510ME), for, in use prior to missile launch, holding the missile canister (510, 512) in a generally vertical launch position below a deck (390). The missile launcher cell (16d) comprises at least one elongated exhaust gas chimney (30d1, 30d2). It also comprises a support structure (14d1, 14d2, 20d1, 20d2) defining a generally axial cavity (418d), also defining a missile launch end and a missile exhaust end. The cavity (418d) of the support structure (14d1, 14d2, 20d1, 20d2) has length and cross-sectional dimensions sufficient to accommodate the missile canister (510, 512). The one or more exhaust chimney (30d1, 30d2)s lie along the exterior of the support structure (14d1, 14d2, 20d1, 20d2) and extend, parallel

JK
6/21/01

00002830 06701
T07290 68220860

with the axis (8d) of the cavity (418d), from
near the missile launch end (300) to near the
missile exhaust end (380) of the support
structure (14d1, 14d2, 20d1, 20d2). The
5 missile launcher cell (16d) also includes a
missile exhaust plenum (40d) attached to the
support structure (14d1, 14d2, 20d1, 20d2) near
the missile exhaust end (380) of the support
structure (14d1, 14d2, 20d1, 20d2). The
10 missile exhaust plenum (40d) is coupled to the
one or more exhaust chimney (30d1, 30d2)(s) near
the missile exhaust end (380) of the support
structure (14d1, 14d2, 20d1, 20d2). The
missile exhaust plenum (40d) further includes
15 an attachment arrangement (360) for attachment
to the missile exhaust end (510ME) of the
missile canister (510, 512), for routing
missile exhaust gas from the missile exhaust
end (380) of the support structure (14d1, 14d2,
20 20d1, 20d2) to the one or more exhaust chimneys
(30d1, 30d2), for causing missile exhaust gas
to vent from the one or more chimneys (30d1,
30d2) near the missile launch end (300) of the
support structure (14d1, 14d2, 20d1, 20d2) of
25 the missile launcher cell (16d). A door or
hatch structure (16dh) is attached to the
missile launch end (300) of the missile launch
cell support structure (14d1, 14d2, 20d1,
20d2), for, in the closed state, protecting at
30 least the support structure (14d1, 14d2, 20d1,
20d2), the one or more chimney (30d1, 30d2)(s)
and any missile canister (510, 512)

↓
6/21/01

↓
6/21/01

0989239-062701

accommodated within the cavity (418d).

In a particular embodiment of the invention, the cavity (418) has a rectangular, or more particularly square, cross-section, and is dimensioned to accommodate a Mk 25 canisterized missile (510,512). The support structure (14d1, 14d2, 20d1, 20d2) may be a latticework. The number of chimneys (30d1, 30d2) in a particular embodiment is two, with the two chimneys (30d1, 30d2) running parallel with each other and with the cavity axis (8d).

In a particularly advantageous embodiment of the invention, an array (10) of missile launcher cells (16a, 16b, 16c, and 16d) has each of the missile launcher cells (16d) of the array dimensioned for accepting a canisterized missile (510, 512), where each missile canister (510, 512) defines a missile launch end (510ML) and a missile exhaust end (510ME). In use prior to missile launch, the array (10) of missile launcher cells (16d) holds the missile canisters (510, 512) in a generally vertical launch position below a deck. Each of the missile launcher cells (16d) includes at least one elongated exhaust gas chimney (30d1, 30d2), and a support structure (14d1, 14d2, 20d1, 20d2) defining a generally axial cavity (418d), and defining a missile launch end (300) and a missile exhaust end (380). The cavity (418d) of the support structure (14d1, 14d2, 20d1, 20d2) of each cell has length and cross-sectional dimensions

09802339-062701
T07290-6326960

structure (14d1, 14d2, 20d1, 20d2) and the one
or more exhaust chimneys (30d1, 30d2) of the
missile launcher cell (16d), and any missile
canister (510, 512) accommodated within the
5 cavity (418d) of the cell, and for, when open,
providing for egress of the missile (512) from
its canister (510) and exhaust gas from the one
or more chimneys (30d1, 30d2). This
arrangement allows the array of missile
10 launchers to be maintained in a condition in
which all of the launcher cells are fitted with
canisterized missiles, without keeping at least
one missile launch cell clear or unloaded so as
to provide a chimney or path for the escape of
15 exhaust gas from a missile fired in a missile
launch cell of the array. Thus, an aspect of
the invention lies in an array of launchers
(10) in which a canisterized missile is located
within each of (all of) the cavities of the
20 array.

00002839-062701